

8oz/270gsm Premium Mesh
PRODUCT: MESH-12
FEATURES / APPLICATIONS:

- 37% air-flow through
- Soft and clean surface
- Printable on two sides with UV ink
- Widely used for scaffolding, theatrical, wall wrapping ,TV backdrops, hanging display& large format advertisement
- A PVC backing is also available which prevents ink spray through when printing and makes the feeding easier

MATERIAL DETAILS

| PROPERTIES | TEST METHOD | METRIC | IMPERIAL |
|------------------|-------------------|---------------------|--------------------|
| Total Weight | DIN EN ISO 2286-2 | 270g/m ² | 8.5oz/sq.yd. |
| Base Fabric | DIN 60001 | Polyester | Polyester |
| Yarn | DIN EN ISO 2060 | 1100 x 1100 dtex | 1000 x 1000 denier |
| Tensile Strength | DIN EN ISO 1421 | 1520x1250 N/5cm | 170x140 lbs/inch |
| Tear Strength | DIN 53363 | 280x223N | 63x50lbs |
| Flame Resistance | DIN 4102 | NFPA 701, B1, M2 | |
| Width | N/A | Max 500cm | 197 inch |

INK PRINTABILITY

| Solvent | Eco Solvent | UV | Latex |
|--------------------------|--------------------------|--------------------------|--------------------------|
| <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| Screen Printing | Dye Transfer | Dye Direct | |
| | | | |

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty

Soyang Technologies Co., Ltd
(Soyang Headquarters)

West 19th FL, Yongtong Information plaza, No. 141 Huancheng Bei Road, Hangzhou City, Zhejiang PR., China.

www.soyang.net

P. 0086-571-28918690

F. 0086-571-28918695

Soyang Haining Factory

No.36 Jinniu Road,Jianshan District,Haining City, Zhejiang PR,China.

Soyang Hangzhou Factory

No,1199 Gongyuan Xi Rd, Fuyang, Hangzhou City, Zhejiang, PR, China

Soyang Europe Ltd

Calder House Metcalf Drive
Altham Industrial estate
Altham Lancashire BB5 5TU UK

www.soyang.co.uk

P. 0044 (0) 161 765 3400

F. 0044 (0) 1282 772982