

6oz/ 210gsm Speak Mesh

PRODUCT: MESH-6

FEATURES / APPLICATIONS:

- A special design to maximize the overall cost
- 80% air -flow through
- Printable on two sides with UV ink
- Excellent printing result
- Widely used for scaffolding, theatrical, TV backdrops, hanging display& large format advertisement
- A PVC backing is also available which prevents ink spray through when printing and makes the feeding easier

MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2	210g/m ²	6oz/sq.yd.
Base Fabric	DIN 60001	Polyester	Polyester
Yarn	DIN EN ISO 2060	1100 x 1100 dtex	1000 x 1000 denier
Tensile Strength	DIN EN ISO 1421	1100x950N/5cm	123x107 lbs/inch
Tear Strength	DIN 53363	250x200N	56x 45lbs
Flame Resistance	DIN 4102	NFPA 701, B1, M2	
Width	N/A	Max 500cm	197 inch

INK PRINTABILITY

Solvent	Eco Solvent	UV	Latex
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Screen Printing	Dye Transfer	Dye Direct	

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty

Soyang Technologies Co., Ltd
(Soyang Headquarters)

West 19th FL, Yongtong Information plaza, No. 141 Huancheng Bei Road, Hangzhou City, Zhejiang PR., China.

www.soyang.net

P. 0086-571-28918690

F. 0086-571-28918695

Soyang Haining Factory

No.36 Jinniu Road,Jianshan District,Haining City, Zhejiang PR,China.

Soyang Hangzhou Factory

No,1199 Gongyuan Xi Rd, Fuyang, Hangzhou City, Zhejiang, PR, China

Soyang Europe Ltd

Calder House Metcalf Drive
 Altham Industrial estate
 Altham Lancashire BB5 5TU UK

www.soyang.co.uk

P. 0044 (0) 161 765 3400

F. 0044 (0) 1282 772982